

S12FV - 24V DC - Zwei-Wege-Magnetventil mit radialer Demontage

2-Wege-Magnetventil mit BSP-Innengewindeanschlüssen.

Funktion: In Ruhestellung geschlossen. Versorgungsspannung: 24V DC



EPDM

Artikel	d	DN	A	B	product.detail.attribute.C	H	product.detail.attribute.H[5:1]	L	Z	E	M	g
S12FV0414E024C	1/4"	4	24	100	103	85	42	11	63	42	52	400
S12FV0438E024C	3/8"	4	24	100	103	86	43	11,5	63	42	52	400
S12FV0614E024C	1/4"	6	24	100	103	85	42	11	63	42	52	400
S12FV0638E024C	3/8"	6	24	100	103	86	43	11,5	63	42	52	400
S12FV0814E024C	1/4"	8	24	100	103	85	42	11	63	42	52	400
S12FV0838E024C	3/8"	8	24	100	103	86	43	11,5	63	42	52	400

S12FV - 24V DC - Zwei-Wege-Magnetventil mit radialer Demontage

Artikel	d	DN	A	B	product.detail.attribute.C	H	product.detail.attribute.H[5:1]	L	Z	E	M	g
S12FV0414F024C	1/4"	4	24	100	103	85	42	11	63	42	52	400
S12FV0438F024C	3/8"	4	24	100	103	86	43	11,5	63	42	52	400
S12FV0614F024C	1/4"	6	24	100	103	85	42	11	63	42	52	400
S12FV0638F024C	3/8"	6	24	100	103	86	43	11,5	63	42	52	400
S12FV0814F024C	1/4"	8	24	100	103	85	42	11	63	42	52	400
S12FV0838F024C	3/8"	8	24	100	103	86	43	11,5	63	42	52	400