

# S12FV - 110V AC - Zweiwege-Magnetventil mit radialer Demontage

2-Wege-Magnetventil mit BSP-Innengewindeanschlüssen.

Funktion: Normalerweise geschlossen. Versorgungsspannung: 110V AC



## EPDM

Artikel	d	DN	A	B	product.detail.attribute.C	H	product.detail.attribute.H[5:1]	L	Z	E	M	g
S12FV0414E110A	1/4"	4	24	100	103	85	42	11	63	42	52	400
S12FV0438E110A	3/8"	4	24	100	103	86	43	11,5	63	42	52	400
S12FV0614E110A	1/4"	6	24	100	103	85	42	11	63	42	52	400
S12FV0638E110A	3/8"	6	24	100	103	86	43	11,5	63	42	52	400
S12FV0814E110A	1/4"	8	24	100	103	85	42	11	63	42	52	400
S12FV0838E110A	3/8"	8	24	100	103	86	43	11,5	63	42	52	400

## S12FV - 110V AC - Zweiwege-Magnetventil mit radialer Demontage

Artikel	d	DN	A	B	product.detail.attribute.C	H	product.detail.attribute.H[5:1]	L	Z	E	M	g
S12FV0414F110A	1/4"	4	24	100	103	85	42	11	63	42	52	400
S12FV0438F110A	3/8"	4	24	100	103	86	43	11,5	63	42	52	400
S12FV0614F110A	1/4"	6	24	100	103	85	42	11	63	42	52	400
S12FV0638F110A	3/8"	6	24	100	103	86	43	11,5	63	42	52	400
S12FV0814F110A	1/4"	8	24	100	103	85	42	11	63	42	52	400
S12FV0838F110A	3/8"	8	24	100	103	86	43	11,5	63	42	52	400