

Microswitch IP 65

PNEUMATICALLY ACTUATED DIAPHRAGM VALVES

MAGNUM 3G is completed with a range of tools and accessories to help the installer

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particularly suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings



Reference	To be used with:	DN
ZMSFC001	DK / NC	15 ÷ 32
ZMSFC002		
ZMSFC003	DKM / NC	40
ZMSFC004	DKM / NC	50 ÷ 65
ZMSFC005	VM / NC	80 ÷ 100
ZMSFC006	DKP / NC	25 ÷ 32
ZMSFC007	DKP / NC	40
ZMSFC008	DKP / NC	50 ÷ 65
ZMSFC009	CM / CP	12 ÷ 15

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations