

S22AV - 24V AC - true union 2-way solenoid valve

2 way solenoid valve with ASTM female union ends for solvent welding.

Function: Normally closed. Power supply: 24V AC

The solenoid valve is the ideal solution for applications requiring many rapid actuation cycles and installations in confined spaces. Thanks to the absence of metal parts in contact with the fluid or the external environment, it can also be used in the presence of aggressive fluids. Ideal for use in fertigation benches.

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
- Lever shutter in EPDM or FKM and lever in stainless steel.
- Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
- Emergency override
- 2-Way PVC-U body
- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
- Adjustable circular section coil with IP65 protection class.
- Integrated override with the possibility of being installed in 3 different positions.
- Lever shutter in EPDM or FKM and lever in stainless steel.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).



EPDM

Reference	d	DN	A	B	C	H	H1	L	Z	E	M	g
S22AV0812E024A	1/2"	8	34	115	130	116	58	22	72	54	67	1000

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations



S22AV - 24V AC - true union 2-way solenoid valve

Reference	d	DN	A	B	C	H	H1	L	Z	E	M	g
S22AV0838E024A	3/8"	8	34	115	130	109	55	19	71	54	67	1000
S22AV1012E024A	1/2"	10	34	115	130	116	58	22	72	54	67	1000
S22AV1038E024A	3/8"	10	34	115	130	109	55	19	71	54	67	1000
S22AV1512E024A	1/2"	15	34	115	130	116	58	22	72	54	67	1000
S22AV1538E024A	3/8"	15	34	115	130	109	55	19	71	54	67	1000

S22AV - 24V AC - true union 2-way solenoid valve

Reference	d	DN	A	B	C	H	H1	L	Z	E	M	g
S22AV0812F024A	1/2"	8	34	115	130	116	58	22	72	54	67	1000
S22AV0838F024A	3/8"	8	34	115	130	109	55	19	71	54	67	1000
S22AV1012F024A	1/2"	10	34	115	130	116	58	22	72	54	67	1000
S22AV1038F024A	3/8"	10	34	115	130	109	55	19	71	54	67	1000
S22AV1512F024A	1/2"	15	34	115	130	116	58	22	72	54	67	1000
S22AV1538F024A	3/8"	15	34	115	130	109	55	19	71	54	67	1000

All information subject to change.

Please contact us on <https://www.aliasis.co.uk/get-in-touch> for further informations

