


Pressure pipe PVC-U PN20 forsheda

Tubo a pressione PVC-U PN20 UNI EN ISO 1452-2 Forsheda 601 Powerlock[®], Grigio RAL 7011, lunghezza 6m.

Pressure pipes for joint system by cold chemical welding (gluing through the use of suitable WELD-ON adhesive and detergent primer) or FORSHEDA 601 POWERLOCK[®] pre-inserted and locked gasket joint.

Lareter rigid PVC pipes for pressure pipes are guaranteed by the certifications issued by IIP, CSTB, DVGW, WRAS and IMO.

- **Size range:** d 16 - d 500 (mm)
- **Nominal pressure:** PN 6-10-12,5-16-20-25 with water at 20° C
- **Temperature range:** 0 °C ÷ 60 °C
- **Coupling standards**
 - **Solvent welding:** EN ISO 15493, EN ISO 1452, DIN 8061/2.
 - **Coupling:** Forsheda 601 POWER-LOCK[®] Gasket
- **Reference standards**
 - **Construction criteria:** EN ISO 15493, EN ISO 1452, DIN 8061/2
 - **Test methods and requirements:** EN ISO 15493, EN ISO 1452, DIN 8061/2
 - **Installation criteria:** DVS 2204, DVS 2221, UNI 11242, EN ISO 1452, DIN 8061/2
- **Pipe material:** PVC-U dark grey RAL 7011



Reference	D (mm)	S (mm)	Lb (mm)	Weight (kg/m)	Qty x pallet
PIPEV11040S6L	40**	3.7*	100	0.65	275
PIPEV11050S6L	50**	4.6*	100	1.00	194
PIPEV11063F6L	63	5.8*	110	1.58	123
PIPEV11075F6L	75	6.8*	120	2.21	87
PIPEV11090F6L	90	8.2*	130	3.19	96
PIPEV13110F6L	110	8.1*	130	3.94	57
PIPEV13125F6L	125	9.2*	150	5.07	51
PIPEV13140F6L	140	10.3*	160	6.43	45
PIPEV13160F6L	160	11.8*	165	8.40	33
PIPEV13200F6L	200	14.7*	180	13.06	20
PIPEV13225F6L	225	16.6*	200	16.53	18
PIPEV13250F6L	250	18.4*	210	20.37	12

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations