

FWAB

Drilling equipment

FWAB drilling equipment for drilling HD-PE pipes in a pressure-free condition:

- FRIALEN spigot saddles SA UNI
- FRIAFIT sewage saddles ASA VL
- Driven by drill

Comprising:

- Hole saw (nominal size-related), hole saw mounting with drill shaft SDS-maximum,
- Extension for hole saw mounting (not for FWAB ASA as well as for SA UNI applications),
- Centring drill with ejector and catch sleeve
- Hexagonal spanner.

Note:

(Fig. shows FWAB 400)



Reference	Short text	Weight [kg]	BX	Pallet quantity
613832	FWAB 90 for FRIALEN SA UNI for d 90	6,400	1	14
613833	FWAB 110 for FRIALEN SA UNI for d 110	12,600	1	15
613834	FWAB 125 for FRIALEN SA UNI for d 125	4,600	1	14
613829	FWAB 160 for FRIALEN SA UNI for d 160	7,000	1	14
613830	FWAB 225 for FRIALEN SA UNI for d 225	13,200	1	14
613831	FWAB 250 for FRIALEN SA UNI for d 250	14,300	1	14
613846	FWAB ASA 160/450 for FRIAFIT ASA VL 160 suitable for pipes up to d 450, SDR 17	11,200	1	14
613816	FWAB ASA 160/710 for FRIAFIT ASA VL 160 suitable for pipes up to d 710, SDR 17	11,200	1	14
613835	FWAB ASA 225 for FRIAFIT ASA VL 225 for d 225	13,200	1	14