

## FWSG SE

### Compact scraper tool for pipe ends and saddle surfaces d 63 - d 315

Dimension-bound scraper tool FWSG SE

- Safe removal of the oxide layer from HD-PE and PE-Xa pipes and in the saddle surface area
- Scraper blade with 2 cutting edges (double life)
- Easy clamping due to the open design of the scraper tool.
- Uniform chip removal by spring-mounted scraper blade
- Delivery in transport box



Reference	Short text	Weight [kg]	BX	Pallet quantity
613562	FWSG SE 63 for d 63	4,100	1	40
613563	FWSG SE 75 for d 75	4,300	1	30
613564	FWSG SE 90 for d 90	4,600	1	30
613565	FWSG SE 110 for d 110	4,600	1	40
613566	FWSG SE 125 for d 125	4,600	1	40
613567	FWSG SE 140 for d 140	4,900	1	30
613568	FWSG SE 160 for d 160	4,900	1	30
613569	FWSG SE 180 for d 180	5,100	1	30
613570	FWSG SE 200 for d 200	5,600	1	30
613571	FWSG SE 225 for d 225	5,600	1	30
613572	FWSG SE 250 for d 250	8,200	1	30
613573	FWSG SE 280 for d 280	8,200	1	30
613574	FWSG SE 315 for d 315	8,200	1	30

## FWSG SE

# Compact scraper tool for pipe ends and saddle surfaces d 63 - d 315

### Application

FRIATOOLS scraper tools for the perfect preparation of HDPE pipe surfaces: Consistently uniform removal of oxide layers for the perfect electrofusion.

### The crucial difference

Having the correct tools to perform installation on site makes all the difference. We see ourselves as specialists in the electrofusion of HDPE piping systems, so our development work has also included equipment and accessories for your needs from the very outset.

We know exactly what matters and what is needed in the field, and we can offer you a range of equipment tailored to the daily challenges encountered on the building site:

FRIATOOLS scraper tools for all pipe diameters and for a wide range of scrape lengths and saddle surfaces. These safeguard a uniform removal of material and reproducible quality for the optimal processing and reliable fusion of HDPE pipes.

Put your trust in tools that produce the perfect results.

### Good reasons for the FRIATOOLS scraper tools FWSG SE:

- Safe and reliable removal of oxide layers on PE 80, PE 100, and PE-X pipes
- Reliable scraping of surface areas of saddle parts on the pipe as well as preparing a fitting fusion on the pipe end
- Spring-loaded and moveable blade support to balance out uneven and bendy pipes
- Simple clamping due to open construction design
- Three grips allow for simple and effort saving turning on the pipe
- Robust and compact design
- Simple handling
- Scraper blade designed as turning blade with 2 cutting edges (twice the service life)
- Delivery in practical aluminum transport case