

FRIAMAT 7 Basic

Fusion unit without documentation function

Powerful universal fusion unit FRIAMAT 7 Basic

- State-of-the-art converter technology with active cooling.
- Bright colour TFT display
- With mini scanner or 1D/2D scanner (2D barcodes according to ISO 12176-5)
- Extra long fusion cable (4 m)
- Extra long power cable (5 m)
- Weight approx. 12.8 kg

Note:

Possibility of updating the FRIAMAT software via the USB interface by the user.



Reference	Short text	Weight [kg]	BX	Pallet quantity
611130	With mini scanner	14,900	1	4
614130	With 1D/2D scanner	14,900	1	4

FRIAMAT 7 Basic

Fusion unit without documentation function

- Powerful electrofusion unit with state-of-the-art converter technology and flow-optimized, active cooling.
- High-resolution, extremely bright 4.3 "TFT color display.
- With mini-scanner, reader wand or new 1D/2D scanner for reading 2D barcodes according to ISO 12176-5, Adapter bag, language selection, adjustable buzzer volume, manual emergency entry. Extra-long power cable (4 m) and extra-long fusion cable (5 m). Weight approx 12,8 kg.
- Continuous monitoring of the entire fusion process and all device functions.
- With FRIAMAT preCHECK function: The most advanced way to fuse with foresight. The FRIAMAT automatically determines whether the next fusion can be performed completely to the end.
- The user himself can install software updates via USB interface.