

# FCIV-PVC-T+magnet

Liquid density: 1kg/l 20 °C - ISO Metric socket unions  
 Float: PP (Polypropylene) red + Magnet



Reference	D	Flow rate range for H[5:2]O [l/h]	B	E	C
FCIV016T1M0015M	16	1,5 - 15	199	165	171
FCIV016T1M0020M	16	2 - 20	199	165	171
FCIV016T1M0050M	16	5 - 50	199	165	171
FCIV016T1M0100M	16	10 - 100	199	165	171
FCIV016T1M0150M	16	15 - 150	199	165	171
FCIV020T1M0025M	20	2 - 25	208	170	176
FCIV020T1M0050M	20	5 - 50	208	170	176
FCIV020T1M0100M	20	10 - 100	208	170	176
FCIV020T1M0150M	20	15 - 150	208	170	176
FCIV020T1M0200M	20	20 - 200	208	170	176
FCIV020T1M0320M	20	30 - 320	208	170	176
FCIV025T1M0080M	25	8 - 80	229	185	191
FCIV025T1M0150M	25	15 - 150	229	185	191
FCIV025T1M0200M	25	20 - 200	229	185	191
FCIV025T1M0350M	25	30 - 350	229	185	191
FCIV025T1M0650M	25	50 - 650	229	185	191
FCIV032T1M0200M	32	20 - 200	250	200	206
FCIV032T1M0300M	32	30 - 300	250	200	206
FCIV032T1M0600M	32	60 - 600	250	200	206
FCIV032T1M1000M	32	100 - 1000	250	200	206

All information subject to change.

Please contact us on <https://www.aliasis.co.uk/get-in-touch> for further informations