

## F3.00.H.XX

### PADDLEWHEEL FLOW SENSOR

#### Paddlewheel Flow Sensor (Remote version)

The simple and reliable paddlewheel flow sensor type F3.00 is designed for use with every kind of solid-free liquids. The sensor can measure flow from 0.15 m/s (0.5 ft/s) producing a frequency output signal highly repeatable. A rugged construction and a proven technology guarantee exceptional performances with little or no maintenance required. A dedicated electronic, with a push-pull output, is available for a safe connection to any kind of PLC/Instrument digital input. A specially designed family of fittings ensures an easy and quick installation into all pipe materials in sizes from DN15 to DN600 (0.5" to 24").


#### APPLICATIONS:

- Water treatment and regeneration
- Industrial wastewater treatment and recovery
- Textile finishing
- Water distribution
- Processing and manufacturing industry
- Filtration systems
- Chemical production
- Liquid delivery systems
- Cooling water monitoring
- Heat Exchangers
- Swimming pools
- Pump protection

#### MAIN FEATURES:

- C-PVC, PVDF or Stainless Steel sensor body
- Two sensor lengths to cover from DN15 up to DN600
- Easy insertion system
- IP65 or IP68 protection class
- Measurement range over 50:1
- High chemical resistance
- Version for battery powered system
- Push-Pull output for universal electrical connection

# F3.00.H.XX



Reference	Version	Power supply	Lenght	Main Wetted Materials	Enclosure	Flow Rate Range	Weight (gr.)
F3.00.H.01	Hall	5 - 24 VCC	L0	C-PVC \$ EPDM	IP68	From 0,15 to 8 m/s*	250
F3.00.H.02	Hall	5 - 24 VCC	L0	C-PVC \$ FKM	IP68	From 0,15 to 8 m/s*	250
F3.00.H.03	Hall	5 - 24 VCC	L1	C-PVC \$ EPDM	IP68	From 0,15 to 8 m/s*	300
F3.00.H.04	Hall	5 - 24 VCC	L1	C-PVC \$ FKM	IP68	From 0,15 to 8 m/s*	300
F3.00.H.05	Hall	5 - 24 VCC	L0	PVDF \$ EPDM	IP68	From 0,15 to 8 m/s*	250
F3.00.H.06	Hall	5 - 24 VCC	L0	PVDF \$ FKM	IP68	From 0,15 to 8 m/s*	250
F3.00.H.07	Hall	5 - 24 VCC	L1	PVDF \$ EPDM	IP68	From 0,15 to 8 m/s*	300
F3.00.H.08	Hall	5 - 24 VCC	L1	PVDF \$ FKM	IP68	From 0,15 to 8 m/s*	300
F3.00.H.09	Hall	5 - 24 VCC	L0	316L SS \$ EPDM	IP68	From 0,15 to 8 m/s*	600
F3.00.H.10	Hall	5 - 24 VCC	L0	316L SS \$ FKM	IP68	From 0,15 to 8 m/s*	600
F3.00.H.11	Hall	5 - 24 VCC	L1	316L SS \$ EPDM	IP68	From 0,15 to 8 m/s*	650
F3.00.H.12	Hall	5 - 24 VCC	L1	316L SS \$ FKM	IP68	From 0,15 to 8 m/s*	650
F3.00.H.13	Hall	5 - 24 VCC	L0	C-PVC \$ EPDM	IP65	From 0,15 to 8 m/s*	250
F3.00.H.14	Hall	5 - 24 VCC	L0	C-PVC \$ FKM	IP65	From 0,15 to 8 m/s*	250
F3.00.H.15	Hall	5 - 24 VCC	L1	C-PVC \$ EPDM	IP65	From 0,15 to 8 m/s*	300
F3.00.H.16	Hall	5 - 24 VCC	L1	C-PVC \$ FKM	IP65	From 0,15 to 8 m/s*	300
F3.00.H.17	Hall	5 - 24 VCC	L0	PVDF \$ EPDM	IP65	From 0,15 to 8 m/s*	250
F3.00.H.18	Hall	5 - 24 VCC	L0	PVDF \$ FKM	IP65	From 0,15 to 8 m/s*	250
F3.00.H.19	Hall	5 - 24 VCC	L1	PVDF \$ EPDM	IP65	From 0,15 to 8 m/s*	300
F3.00.H.20	Hall	5 - 24 VCC	L1	PVDF \$ FKM	IP65	From 0,15 to 8 m/s*	300
F3.00.H.21	Hall	5 - 24 VCC	L0	316L SS \$ EPDM	IP65	From 0,15 to 8 m/s*	600

All information subject to change.

Please contact us on <https://www.aliasis.co.uk/get-in-touch> for further informations



## F3.00.H.XX

Reference	Version	Power supply	Lenght	Main Wetted Materials	Enclosure	Flow Rate Range	Weight (gr.)
F3.00.H.22	Hall	5 - 24 VCC	L0	316L SS \$ FKM	IP65	From 0,15 to 8 m/s*	600
F3.00.H.23	Hall	5 - 24 VCC	L1	316L SS \$ EPDM	IP65	From 0,15 to 8 m/s*	650
F3.00.H.24	Hall	5 - 24 VCC	L1	316L SS \$ FKM	IP65	From 0,15 to 8 m/s*	650

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations

