

M9.03.PX – M9.03.WX

Dual Flow Monitor and Transmitter

Dual Flow Monitor and Transmitter

FLS M9.03 is a powerful dual flow monitor designed to convert the frequency signals of FLS flow sensors into flow rates. M9.03 is equipped with a 4" wide full graphic display which shows measured values clearly and a lot of other useful information. Moreover, due to a multicolor display plus a powerful backlight, measurement status can be determined easily from afar also. A tutorial software guarantees a mistake-proof and fast set up of every parameters. Calibrations can be performed just fixing installation features or using a reference value through a new "in-line calibration". Two 4-20mA output are available to remote each flow rate to an external device. A proper combination of digital outputs allows customized setups for any process to be controlled. The USB port on the rear part allows the upgrade of software offering a wide range of customization services both standard and on request.

APPLICATIONS:

- Water treatment systems
- Industrial waste water treatment and recovery
- Water distribution
- Filtration systems
- Swimming pools & SPA
- Irrigation & Fertigation
- Leak detection
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight
- Help on board
- Delta flow rates visualization
- Fast, intuitive and mistake-proof calibration software
- Mechanical relays for external device control
- Solid State Relays for programmable alarms
- Multilanguage menu
- USB port for software upgrading

All information subject to change.

Please contact us on <https://www.aliasis.co.uk/get-in-touch> for further informations

M9.03.PX – M9.03.WX



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.03.P1	Panel	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.03.W1	Wall	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.03.W2	Wall	110 - 230 VCA	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations