

M9.10.PX – M9.10.WX

Dual Analog Monitor and Transmitter

Dual Analog Monitor and Transmitter

FLS M9.10 is a powerful monitor and transmitter designed to manage analog and frequency signals (or two analog signals) from every types of device which provide a 4-20mA or a frequency output. M9.10 is equipped with a wide full graphic display 4" which shows measured values clearly and a lot of other useful information. Moreover, due to a multicolor display plus a powerful backlight, measurement status can be determined easily from afar also. A tutorial software guarantees a mistake-proof and fast set up of every parameters. Calibration of 4-20mA input can be performed just fixing 2 points as well as 1 point or using a reference value through a new "in-line calibration". Calibration of frequency input can be performed just fixing installation features or using a reference value through a new "in-line calibration". Two independent 4-20mA outputs are available to remote measures to external devices. A proper combination of digital outputs (2*SSR and 2*relays) allows customized setups for any process to be controlled. The USB port on the rear part allows the upgrade of software offering a wide range of customization services both standard and on request.

APPLICATIONS:

- Industrial waste water treatment
- Civil waste water treatment
- Water treatment processes
- Processing and Manufacturing industry
- Chemical processing
- Industrial environment with electromagnetic interferences

MAIN FEATURES:

- Wide graphic display
- Multicolor backlight
- Help on board
- Simultaneous visualization of two parameters
- Free setting of engineering unit
- Intuitive calibration procedure
- In line adjustment
- Able to handle active and passive analog signal
- USB port for software upgrading

All information subject to change.

Please contact us on <https://www.aliaxis.co.uk/get-in-touch> for further informations

M9.10.PX – M9.10.WX



Reference	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.10.P1	Panel	12 - 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.10.W1	Wall	12 - 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.10.W2	Wall	110 - 230 VCA	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750

All information subject to change.

Please contact us on <https://www.aliasis.co.uk/get-in-touch> for further informations