

# S22AV - 110V AC - valvola a solenoide a due vie a smontaggio radiale

Valvola a solenoide a 2 vie, con attacchi femmina ASTM a bocchettone per incollaggio.

Funzione: Normalmente Chiusa. Tensione di alimentazione: 110V AC



## EPDM

Codice	d	DN	A	B	C	H	H	L	Z	E	M	g
S22AV0812E110A	1/2"	8	34	115	130	116	58	22	72	54	67	1000
S22AV0838E110A	3/8"	8	34	115	130	109	55	19	71	54	67	1000
S22AV1012E110A	1/2"	10	34	115	130	116	58	22	72	54	67	1000
S22AV1038E110A	3/8"	10	34	115	130	109	55	19	71	54	67	1000
S22AV1512E110A	1/2"	15	34	115	130	116	58	22	72	54	67	1000
S22AV1538E110A	3/8"	15	34	115	130	109	55	19	71	54	67	1000

## FKM

Codice	d	DN	A	B	C	H	H	L	Z	E	M	g
S22AV0812F110A	1/2"	8	34	115	130	116	58	22	72	54	67	1000
S22AV0838F110A	3/8"	8	34	115	130	109	55	19	71	54	67	1000
S22AV1012F110A	1/2"	10	34	115	130	116	58	22	72	54	67	1000
S22AV1038F110A	3/8"	10	34	115	130	109	55	19	71	54	67	1000
S22AV1512F110A	1/2"	15	34	115	130	116	58	22	72	54	67	1000
S22AV1538F110A	3/8"	15	34	115	130	109	55	19	71	54	67	1000